WAFER LED I SURFACE MOUNT


57720 / 57722 / 57724

- Die Cast Aluminum
- Size options between 4.5", 6.25" and 9"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location
- ETL/cETL IP65



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT
57720	4.5"L x 4.5"W x 0.5"H	0.99 lb
57722	6.25"L x 6.25"W x 0.5"H	1.21 lb
57724	9"L x 9"W x 0.5"H	1.80 lb

LAMPING

			LUMENS	COL			
	MODEL	BULB TYPE	CRI	INIT DEL	TEMP.	DIMMABLE	INPUT
	57720	10W PCB LED (Integrated)	90+	700 600	3000K	ELV	120V
	57722	15W PCB LED (Integrated)	90+	1050 900	3000K	ELV	120V
	57724	20W PCB LED (Integrated)	90+	1400 1200	3000K	ELV	120V

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

White (WT)
Bronze (BZ)

Job Name : _____

Job Type : _____

Quantity : _____

Comments:

Satin Nickel (SN)



MATERIAL:

Die Cast Aluminum PMMA Acrylic Diffuser

AVAILABLE SIZES:

4.5" | 6.25" | 9"

RATINGS:

ETL/cETL IP65
Wet Location
Energy Star
Title 24 JA8 compliant
ADA
Closets Rated: NEC 410.8 & 410.16









ADDITIONAL:

RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online



4200 SHIRLEY DR. I ATLANTA, GA 30336