DIVERSE LED 7.5" I CONCAVED LENS I SURFACE MOUNT

57651 / 57652 / 57654

- Slim design makes it a great substitute for recessed lighting
- Fully dimmable with CL Triac Dimmers
- High powered LEDs create a brighter shine
- Approved for use in closets and storage spaces
 Reduces energy consumption and operating costs by up
- to 80% over incandescent downlights
- Easy to install: fits all standard 3" or 4"J-box
- Suitable for wet locations
- Innovative design runs cooler to maximize energy efficiency
- High-powered LED output creates brighter shine
- Energy Star Certified, CRI 90+
- ETL/ cETL IP65

- Job Name : _____
- Job Type 🛛 : ____
- Quantity : ___
- Comments : ____




Flush Mount with a concaved lens

FINISHES OPTIONS:

PRODUCT DESCRIPTION

The Diverse LED Flush Mount is constructed of die-cast aluminum and is fully sealed for use in ceiling and wet location instalations. This innovative design reduces operating costs by up to 80% over incandescent downlights.




MEASUREMENTSDIMENSIONS: 7.5"D x 0.75"HHANGING WEIGHT: 0.54 lb

LAMPING

			LUMENS		COL	
MODEL	BULB TYPE	CRI	RATED	DEL	TEMP. DIMMABLE	INPUT
* 57651	(1) 12.5W LED (Integrated)	90+	1100	900	2700K Triac Dimmer	120V
57652	(1) 12.5W LED (Integrated)	90+	1100	950	3000K Triac Dimmer	120V
* 57654	(1) 12.5W LED (Integrated)	90+	1100	990	4000K Triac Dimmer	120V

 * Available in White (WT) finish only. Contact our Representative for special requests (MOQ may apply).

ACCESSORIES (Sold Separately):



RFK57652 Retrofit Conversion Kit



MSC030 3.0" Mounting Bracket

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com



*57651 & 57654

Bronze (BZ)*

White (WT)

Satin Nickel (SN)*

Available in White (WT) finish only. Contact our Representative for special requests (MOQ may apply).

MATERIAL: Aluminum + Acrylic Diffuser

RATINGS:

ETL/cETL IP65 Wet Location Dimmable With Triac Dimmer Energy Star Closets Rated: NEC 410.8 & 410.16



ADDITIONAL: RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online